

## PROCUREMENT QUALITY CLAUSES: PQC-1

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**This document establishes the Procurement Quality Clauses (PQC-1) that are applicable as specified on the AMETEK SCP, Inc. Purchase Order. In ALL cases the NOTES immediately below APPLY to every Purchase Order:**

- NOTE 1:** To ensure you have the latest version of the Procurement Quality Clauses for AMETEK, SCP, Inc., please go to the AMETEK, SCP website at: <http://www.ametek-ecp.com/Brands/SCP.aspx>, scroll to bottom of page to Downloads, Click on Downloads, and select the AMETEK SCP Quality Clauses.
- NOTE 2:** The Supplier must flow down to any subcontractors the requirements of the PQC-1 clauses on the purchase order that apply to those subcontractors.
- NOTE 3:** Malpractice is an instance of negligence or incompetence on the part of a professional and suppliers must avoid the slightest possibility or appearance of Malpractice. Therefore, suppliers must be vigilant that all documents are accurate and free from errors and must have documented procedures and training programs to prevent malpractice.
- NOTE 4:** Order of Precedence- In the event of conflicts and/or disputes regarding requirements, the Customer Contract or Purchase Order is the highest level requirement in the order of precedence.
- NOTE 5: DEFENSE PRIORITIES AND ALLOCATION SYSTEM (DPAS)**
- A. “DX” RATED ORDERS**  
This purchase order supports a “rated order” Contract certified for national defense, emergency preparedness, and energy program use and the supplier shall follow all the requirements of the Defense Priorities and Allocation System Regulation 15 CFR Part 700. The supplier shall accept or reject the rated order and transmit the acceptance or rejection in writing (hard copy), or in electronic format within ten (10) days of receipt of order.
- B. “DO” RATED ORDERS**  
This purchase order supports a “rated order” Contract certified for national defense, emergency preparedness, and energy program use and the supplier shall follow all the requirements of the Defense Priorities and Allocation System Regulation 15 CFR Part 700. The supplier shall accept or reject the rated order and transmit the acceptance or rejection in writing (hard copy), or in electronic format within fifteen (15) days of receipt of order.
- NOTE 6: Any deviations from the drawing or specification must be communicated to AMETEK SCP:**
- A.** Prior to manufacture, all non-compliances shall be submitted to the buyer in the form of a Deviation using Government form DD 1694 or supplier equivalent. This will result in a Stop Work pending approval.
- B.** Non-compliances found after manufacture shall be submitted to the buyer in the form of a Waiver using Government Form DD 1694 or supplier equivalent. This will result in a Stop Work pending approval.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**01. INSPECTION SYSTEM REQUIREMENTS**

**A. HIGHER LEVEL QUALITY REQUIREMENTS**

The Seller shall establish and maintain an inspection system that complies with specifications MIL-Q-9858, MIL-I-45208, ISO9001, or other acceptable standard. Satisfactory compliance with this requirement does not relieve the Seller of the responsibility to furnish acceptable parts or services as specified in the procurement documents.

**B. COMMERCIAL INSPECTION SYSTEM**

The Seller shall establish and maintain an inspection system to assure product compliance with drawing, specification, and purchase order requirements. Satisfactory compliance with this requirement does not relieve the Seller of responsibility to furnish acceptable parts or services as specified in the procurement documents.

**02. CERTIFICATE OF CONFORMANCE**

Each shipment must be accompanied by a Certificate of Conformance stating that the material supplied conforms to all purchase order, drawing, and specification requirements. The certification must identify part numbers, part names, material heat/lot numbers, serial numbers, quantities, date, seller's company name, address & phone number, and the printed name, title, and signature of an authorized representative of the Seller, on the Buyer's purchase order.

**Note:** Parts and/or assemblies may not vary from applicable drawings, specifications, etc. in material, dimensions, configuration, process, identification, testing, certification or any other requirements without specific approval in advance, in writing, signed by AMETEK SCP Engineering and Quality Assurance.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**03. NOT USED**

**04. MATERIAL TRACEABILITY**

Parts manufactured for this purchase order must be traceable to raw material used. All parts are to be segregated by heat or lot number and shipping containers identified with the applicable heat or lot number. If specified in the purchase order, parts are to be marked with the heat or lot number as described in the purchase order. A Certificate of Conformance containing the heat or lot number of material must be supplied with each shipment.

- A. If the material is supplied by the Seller, chemical and physical test reports for raw materials must be on file and available for review by the Buyer's Quality Representative upon request.
- B. If the parts or material are supplied by AMETEK SCP, Inc. the Seller shall supply a certification stating that only the parts or material furnished were used in the performance of the Purchase Order. The certification shall contain the heat/lot number of the material used or serial numbers of the parts supplied by AMETEK SCP, Inc.

**05. IDENTIFICATION OF LIMITED SHELF LIFE MATERIALS**

The Seller shall identify each container or package of limited shelf life materials with the date of manufacture, expiration date, special storage conditions (if required), lot number, name, type, and quantity. The certification for material supplied shall also include this information.

**Note:** With the exception of O-rings and packings, material must have at least 80% of its shelf life remaining when received by AMETEK SCP, Inc.

**O-RINGS and PACKINGS**

- A. Sellers of rubber O-rings and packings shall provide certification that the material furnished is in accordance with the applicable specification requirements. The certification shall include PO number, material description, specification number and revision, lot number and cure date. The cure date shall be no greater than seven years from the ship date.
- B. Same as "05A", except that the cure date shall be no greater than three years from the ship date.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**06. CHEMICAL AND PHYSICAL TEST REPORTS**

Each shipment must be accompanied by physical and/or chemical test reports required by the specification referenced in the purchase order. The test reports must bear the printed name, title and signature of an authorized representative of the agency performing the test. In the case of raw materials each part shall be marked with the heat and/or lot number. In the case of parts or assemblies, each part, assembly, container or package of material shall be identified with the heat and/or lot number.

**07. TEST REPORTS**

Each shipment shall contain a test report(s), identifiable to the submitted material by part number(s) and serial number(s), confirming that the required design and operation tests have been performed and that the applicable data, such as hydrostatic or operation pressures, hydraulic or pneumatic flows, pressure drops, temperatures, megger readings, power, voltages, currents, frequencies, rpm loads, strengths, time, etc. have been recorded. The certification shall contain printed name, title, and signature of an authorized representative confirming that the reports of the tests are on file and that the results of the tests conform to the requirements of the purchase order.

**08. NOT USED**

**09. MERCURY FREE CLAUSE**

Each shipment shall contain a certification stating that the material supplied on the purchase order shall be mercury-free and shall conform to the clauses specified herein.

DEFINITION: Mercury-Free is material that does not contain functioning mercury and is not contaminated by mercury or mercury containing compounds.

Mercury or mercury containing compounds shall not be intentionally added or come in contact with hardware or supplies furnished under this contract.

The presence of mercury in a product may be determined by checking product labeling or material safety data sheets. Chemical analysis is not required.

Reference: [NAVSEAINST 5100.3D](#)

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**10. CALIBRATION SYSTEM REQUIREMENTS**

The seller shall establish and maintain a calibration system that complies with ANSI/NCSL Z540, ISO10012, or ANSI/ISO/IEC 17025. Records of calibration shall be maintained and available for review.

Tooling/equipment used to take measurements or values recorded on reports or documents must be listed on the report or document. Listing must include tool number, calibration date and recalibration due date.

**11. NONDESTRUCTIVE TEST REPORTS**

Each shipment must contain a test report containing the actual results of all required nondestructive tests performed. The report shall identify the date tested, the material by part number, part name, serial number(s), material heat number(s) and quantity. If multiple heat numbers are used, the report must clearly indicate which serial number(s) relate to which heat number(s). The report shall list the test specification, approved procedure identification, the acceptance criteria, type and method used and the accept/reject status of the material tested. The report shall call out the applicable revisions and amendments of all specifications and procedures listed and bear the printed name, title, and signature of the authorized representative of the agency performing the test(s). For dye penetrant test, all chemicals used must be listed with brand, type and batch numbers and must be listed on AMS2644 QPL (QPD-2644). Parts tested must be uniquely identified with a serial number. All testing must be accomplished using approved NDT procedures. Vendors must supply inspector vision test and qualification data covering all procedures/tests performed, such as liquid penetrant testing, visual weld inspection, ultrasonic testing, etc. The assigned quality clause on the Purchase Order may contain multiple requirements such as 11A, 11B, 11D & 11F.

A. Dye Penetrant Testing in accordance with NAVSEA T9074-AS-GIB-010/271, Change Notice 1; Type II (Visible Dye), Method "A" (Water Washable).

1. This Method "A" shall not be used on welds. This Method "A" is approved for inspection of threads. This method may be used for the entire part under test. **This Method "A" shall be accomplished prior to welding to ensure all surfaces are inspected.**

B. Dye Penetrant Testing in accordance with NAVSEA T9074-AS-GIB-010/271, Change Notice 1; Type II (Visible Dye), Method "C" (Solvent Removable).

1. This Method "C" shall not be used for threaded surfaces. This Method "C" is approved for inspection of welds. This method may be used for all but threaded surfaces. **This method is commonly accomplished post welding (root and final pass as applicable) or for parts without threads.**

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

C. Dye Penetrant Testing in accordance with NAVSEA T9074-AS-GIB-010/271, Change Notice 1; Type III (Visible and Fluorescent Dye – dual mode), Method “A” (Water Washable).

1. This Method “A” shall not be used on welds. This Method “A” is approved for inspection of threads. This method may be used for the entire part under test. **This Method “A” shall be accomplished prior to welding to ensure all surfaces are inspected.**

D. Visual Testing of root weld (layer) in accordance with NAVSEA S9074-AR-GIB-010/278, Class A-2, para 10.3.3, Table X, Note 3.

1. A Visual test of the root weld (e.g. cover on hull penetrator) at 5X magnification may be substituted for an MT/PT inspection

E. Ultrasonic Testing of raw material prior to machining in accordance with NAVSEA T9074-AS-GIB-010/271, Change Notice 1.

F. Ultrasonic Testing of raw material prior to machining in accordance with NAVSEA T9074-AS-GIB-010/271, Change Notice 1; **Longitudinal Wave method required.**

**12. SOURCE INSPECTION OPTION**

AMETEK SCP, Inc. and its customers reserve the right to inspect any of the materials and associated documentation covered by this purchase order at the supplier's facilities. An advance notice of 48 hours will be provided to the supplier when this option is to be exercised.

**13. GOVERNMENT SOURCE INSPECTION OPTION**

The Government reserves the right to inspect and/or test all or any of the materials covered by this purchase order at the supplier's facility.

**14. SOURCE INSPECTION REQUIRED**

All items covered by this purchase order are subject to source inspection at the supplier's facility prior to shipment. This may include witnessing of tests or inspections, surveillance of quality systems and procedures, and surveillance of manufacturing facilities cost, the necessary equipment, facilities, and Purchase Order requirements. The seller must obtain the dated stamp and/or signature of the source inspector on the applicable test, inspection or certification documents as well as on the shipping document prior to shipment of material. Failure to do so will result in rejection of the material at receiving inspection.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**15. GOVERNMENT SOURCE INSPECTION REQUIRED**

All parts and services covered by this purchase order will be subject to inspection and/or test by the Government prior to shipment from your plant. It is the seller's responsibility to notify the Government. Upon receipt of this order, promptly notify the Government Representative who normally services your plant so that appropriate planning for Government inspection can be accomplished. The seller must obtain the Government's Representative's dated stamp and/or signature on the applicable test, inspection or certification documents as well as on the shipping document prior to shipment of material. Failure to do so will result in rejection of the material at receiving inspection.

**16. NOT USED**

**17. FIRST PIECE INSPECTION**

The seller shall manufacture and submit for approval a first piece. The first piece should be manufactured utilizing the methods to be used on the remaining production lot. The manufacture of production units prior to approval of the first piece shall be at the sole risk of the Seller.

**18. QUALITY REQUIREMENTS FOR CALIBRATION SERVICES**

All calibration performed for AMETEK SCP, Inc. shall be accomplished in strict conformance to ANSI/NCSL Z540 or ANSI/ISO/IEC 17025 in effect at the time of order. Certification of calibration is required with this order. Certification must conform to ANSI/ISO/IEC 17025 Paragraph 5.10 excepting 5.10.3.

In addition to the information required above, the calibration certification shall include a statement to the effect that the standards used in obtaining the results have been compared or are traceable to the NIST standards. All items calibrated shall have a tag or label applied that includes the name of the company performing the calibration, the date calibrated and the recalibration due date.

**19. LEVEL 1/SUBSAFE**

The material covered by the purchase order will be used in a crucial shipboard system. The use of incorrect or defective materials would create a high probability of failure, resulting in serious personal injury, loss of life, loss of vital shipboard systems, or loss of the ship itself. Therefore, the following guidelines must be met:

The requirements of AMETEK SCP Quality Instruction QI-1000 must be met.

If raw material is to be supplied, the requirements in DI-MISC-81020 form a part of this order.

Non-Level 1/SUBSAFE items that have a direct bearing on Level 1/SUBSAFE parts, such as Test Specimens for Tensile Testing or Material Certification shall be treated the same as Level 1/SUBSAFE parts or material.



*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**20. SAFETY DATA SHEETS (SDS)**

As required under the OSHA Hazard Communication Standard 29 CFR 1910.1200(g)(7)(i), a Safety Data Sheet (SDS) must be provided with the first shipment of any hazardous material defined as such under OSHA. For items previously ordered, an SDS must also be supplied if the SDS has changed since the previous shipment.

**21. CABLE LENGTH REQUIREMENT**

Cable length shall be marked on the individual reels and accompanying paperwork. No multiple lengths are allowed on a reel. Both ends of each cable on a reel must be exposed. Maximum size of reel shall be 54" high, 38" wide. Weight of reel shall not exceed 1500 lbs.

**22. QUALIFIED PRODUCTS**

Manufacturers of products supplied must be on the Qualified Product List (QPL) and supply certification. Any supplier that makes any changes to a product on the QPL, such as changes to the material, chemical content, dimensions, testing, process, etc., not specifically authorized by the certifying agency, shall not deliver the affected product as a QPL item without proof of recertification.

**23. INSPECTION DATA REPORTS**

Inspection data (dimensions) shall be provided with each shipment.

- A. For Level 1/SUBSAFE material, actual dimensions of all parts are required for the following characteristics:
  - 1. Dimensions with a tolerance of  $\pm .005''$  or less.
  - 2. Straightness of  $.010''$  per foot or less.
  - 3. Geometric characteristics (forms, profile, location, run out, etc.) with a tolerance of  $.010''$  or less.
  - 4. Finishes of  $32 \mu$  inches or less.
  - 5. Angles with tolerance of  $\pm \frac{1}{2}$  degree or less.
  - 6. All threads shall have major (external thread) and minor (internal threads) diameters measured.
- B. For non-Level 1/SUBSAFE parts dimensions need be supplied for only one piece using the criteria in A. above.
- C. 100% actual dimensions to be supplied for one piece.
- D. 100% actual dimensions to be supplied for all pieces.
- E. Actual dimensions as specified on AMETEK SCP supplied list to be supplied for all pieces.



*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**24. BUY AMERICAN**

Supplies procured on this purchase order must comply with Defense Acquisition Regulations System (DFARS) 252.225-7001 Buy American Act.

**25. NOT USED**

**26. TYPE 3.2 MATERIAL CERTIFICATION**

Material supplied with this clause invoked shall be in accordance with BS EN10204, 3.2 requirements, and shall have independent third party witnessing by an IACS accredited organization. Witnessing is required for:

- any laboratory testing verification of the parent material
- any separation of material from the parent (i.e. lab sample and smaller batches (parent/child))
- material that will undergo a manufacturing process that will alter the mechanical properties of the material.

**NOTE:** AMETEK SCP will provide clarification on Type 3.2 or Upgrading Type 3.1 to the intent of Type 3.2 certification.

**27. NOT USED**

**28. WELDING PROCEDURE QUALIFICATION RECORDS, WELDING PROCEDURE SPECIFICATIONS, WELDER PERFORMANCE QUALIFICATION RECORDS, & WELDING FABRICATION AND INSPECTION**

**WELDING PROCEDURE QUALIFICATION RECORDS:**

The supplier shall provide a Procedure Qualification Record (PQR) in accordance with NAVSEA Technical Publication S9074-AQ-GIB-010/248. The PQR shall consist of a record of the actual parameters used for welding the procedure qualification test assembly, copies of the original test reports, and any other supporting documentation. The PQR shall be uniquely identified and each page of the PQR package shall be dated and contain unique PQR identification. Qualification data shall identify the test assembly weld joint in accordance with MIL-STD-22D. Base metal used in the qualification shall be a listed S-numbered base material in Table I of S9074-AQ-GIB-010/248 when the production application uses a listed material. Cleaning methods shall be described in all PQRs. A copy of the original NDT report shall be submitted with the qualification data and NDT shall be performed in accordance with S9074-AS-GIB-010/271 with acceptance criteria in accordance with MIL-STD-2035, Class I. A copy of the original destructive test report shall be submitted with the qualification data. Destructive testing shall be performed in accordance with AWS B4.0 and acceptance criteria shall be in accordance with S9074-AQ-GIB-010/248, paragraph 4.5.2 and associated subparagraphs. A Certification Statement shall be provided stating the following: "I certify that the tests and the test results meet all requirements of S9074-AQ-GIB-010/248 and that the welding procedure meets all

## PROCUREMENT QUALITY CLAUSES: PQC-1

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

requirements of S9074-AQ-GIB-010/248 and S9074-AR-GIB-010/278." (or T9074-AD-GIB-010/1688 as applicable). PQRs may be generated using software such as NavWeld (<http://www.weldqc.com/>).

### **WELDING PROCEDURE SPECIFICATIONS:**

The supplier shall provide a Welding Procedure Specification (WPS) in accordance with NAVSEA Technical Publication S9074-AQ-GIB-010/248. Each procedure shall be uniquely identified and each page of the procedure shall be dated and contain the unique procedure identification and revision identification. The procedure shall also reference the number of the supporting PQR. Base materials for non-special weld procedures shall utilize materials specifically listed in Table I of S9074-AQ-GIB-010/248. Filler materials used in production welding shall be procured in accordance with the specified Military specification and type listed in Table II of S9074-AQ-GIB-010/248. The procedure shall specify those joint designs that the supplier will be welding or shall specify the joint designs that the procedure is not qualified to perform. The cleaning requirements of S9074-AR-GIB-010/278, paragraph 7.2 (or T9074-AD-GIB-010/1688, paragraph 14.2.2, as applicable) shall be included in all welding procedures. Welding procedures may be generated using software such as NavWeld (<http://www.weldqc.com/>).

### **WELDER PERFORMANCE QUALIFICATION RECORDS:**

Welder Performance Qualification Records (WPQR) shall be submitted in accordance with NAVSEA Technical Publication S9074-AQ-GIB-010/248 and shall be submitted for each welder. Welder Performance Qualifications may be generated using software such as NavWeld (<http://www.weldqc.com/>).

### **WELDING FABRICATION, INSPECTION, AND REPAIR:**

The supplier shall perform welding and welding inspection in accordance with NAVSEA Technical Publication S9074-AQ-GIB-010/278. Written procedures shall be approved by the buyer's Approval Authority prior to performance of welding and shall be submitted for approval thirty (30) days prior to the supplier's anticipated start of work. Procedures and qualification reports shall list the specification revision used. Unless otherwise approved, no less than two layers or weld passes shall be used for all pressure containing Seal Weld joints. For material being supplied in support of orders for General Dynamics Electric Boat (GDEB) or others purchasing a M24231/11 style penetrator that has receptacles the following applies for receptacle welding:

- a) Clean by vapor de-grease method or equal.
- b) Clean prior to welding
- c) Size of fillet weld 3/16-inch. Total of three beads.
- d) Liquid Penetrant inspect (P.T.) root and final weld.
- e) Apply weld in quadrants 3/4-inch (maximum) long opposite each other until weld is complete –OR– Weld to be applied in quadrants opposite each other until weld is complete.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

- f) Exercise caution during welding procedure to control temperature build-up in order to prevent any distortion of receptacles.
- g) Recommended inter-pass temperature is 80 to 90°F.

Weld defects detected by visual test (VT) or other NDT methods, shall be removed and repaired only to the extent necessary to render the area acceptable. NDT shall be performed in accordance with T9074-AS-GIB-010-271. Completed weld repairs of weld defects shall be inspected by the same nondestructive method required for the original weld. Base metal surface defects and damaged base material may be repair welded provided the repair weld and adjacent metal is inspected by the same methods as required for the class of welding. Visual Test (VT) inspection shall be performed using a written procedure and qualified personnel in addition to the requirements of T9074-AS-GIB-010-271. VT inspection of welds shall be performed after slag removal and with the weld in the final surface condition.

## **29. PARTS TRACEABILITY**

### **A. SERIAL NUMBERS**

When serial number(s) are required by drawing, specification, purchase order or contract, they shall be furnished to suppliers on the applicable AMETEK SCP purchase order. If they have not been furnished, the supplier is to request them from AMETEK SCP Purchasing. **SUPPLIERS SHALL NOT CREATE THEIR OWN SERIAL NUMBERS.** Serial number(s) shall be marked on the parts as indicated on the applicable drawing, specification, etc.

On orders for outside processes, such as engraving, coating, plating, etc. where the parts are furnished to the supplier by AMETEK SCP, either directly or drop shipped from another supplier, the serial number(s) for all parts involved shall be listed on the AMETEK SCP purchase order.

### **B. LOT NUMBERS**

Parts which are not serialized shall be identified by lot numbers. A lot may contain differing quantities of parts. Lot numbers, if not designated by AMETEK SCP, may be assigned by the supplier. All parts in a lot shall be made from the same heat or lot of material, and shall not be intermixed either by the original supplier, by AMETEK SCP or by other suppliers performing subsequent operations on the parts. All parts shall have their packaging or tags clearly marked with the applicable lot number(s).

On orders for outside processes, such as engraving, coating, plating, etc. where parts are furnished to the supplier by AMETEK SCP, either directly or drop shipped from another supplier, lot number(s) for all parts shall not be intermixed during processing or packaging.

### **C. DOCUMENTATION**

Serial number(s) or lot number(s), as applicable, shall appear on all related documentation for the each order, such as Certificates of Conformance, NDT reports

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

(dye penetrant, ultrasonic, etc.), inspection reports, weld reports, plating and coating documents, etc.

Weld reports and dye penetrant reports must list all component parts of each assembly, indicating the part name, part number, material heat/lot number and serial number of each component.

**D. PARTS ORDERED “LESS MARKING”**

Parts ordered “less marking” require proper traceability until such time as they are permanently marked. These parts must be identified with temporary marking of the applicable part number(s), material heat/lot number(s) and serial number(s). The temporary marking may be accomplished using a paint marker or equivalent directly on the part(s) or by marking on a tag(s) attached to the part(s). Small part(s) may have the information applied to a bag or other packaging containing the part(s).

**30. MATERIAL TYPE**

- A.** Penetrator Bodies to be manufactured using Nickel-Copper-Aluminum, alloy Monel K-500, in accordance with QQ-N-286G or newer; Form 2, Annealed and Age Hardened, and Guide Pins to be manufactured using Nickel-Copper, alloy Monel 400, in accordance with QQ-N-281D, Amendment 2 or newer; Class A, Form 1, Cold Drawn, Stress Relieved.
- B.** Penetrator Bodies to be manufactured using Nickel-Copper-Aluminum, alloy Monel K-500, in accordance with QQ-N-286G or newer; Form 2, Annealed and Age Hardened.
- C.** Parts to be manufactured using Nickel-Copper-Aluminum, alloy Monel K-500, in accordance with QQ-N-286G or newer; Form 2, Annealed and Age Hardened.
- D.** Receptacle Bodies and Guide Pins to be manufactured using Nickel-Copper, alloy Monel 400, in accordance with QQ-N-281D, Amendment 2 or newer; Class A, Form 1, Cold Drawn, Stress Relieved.
- E.** Parts to be manufactured using Nickel-Copper, alloy Monel 400, in accordance with QQ-N-281D, Amendment 2 or newer; Class A, Form 1, Cold Drawn, Stress Relieved.
- F.** Parts to be manufactured using Nickel-Copper, alloy Monel 400, in accordance with QQ-N-281D, Amendment 2 or newer; Class A, Form 1, Hot Finished.
- G.** Parts to be manufactured using Nickel-Aluminum-Bronze, alloy C63200, in accordance with QQ-C-465B, Amendment 1 and ASTM B150/B150M-08 or newer.
- H.** Parts to be manufactured using Nickel-Aluminum-Bronze, alloy C63000, in accordance with QQ-C-465B, Amendment 1 and ASTM B150/B150M-08 or newer.
- J.** Part(s) to be manufactured using Steel, alloy HY-80, in accordance with MIL-S-21952D and NAVSEA T9074-D-GIB-010/0300.
- K.** Part(s) to be manufactured using Stainless Steel, alloy 316L, in accordance with QQ-S-763F and AMS-QQ-S-763 rev. B or newer.

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

**31. NOT USED**

**32. NOT USED**

**33. NOT USED**

**34. NOT USED**

**35. RECORD RETENTION**

Records shall be retained by the supplier as follows: 1) Calibration Certificates – life plus one year, 2) Calibration Records – life plus one year, 3) Corrective Action Requests – 7 years, 4) Purchase Order – 7 years, 5) Deviations and Waivers – 7 years, 6) Engineering Change Order – permanent, 7) Inspection Record – 7 years, 8) Audit Reports – 7 years, 9) Training Records – employment plus 1 year, 10) Material Traveler – 7 years, 11) Nonconformance Report – 7 years, 12) Manufacturing Routers – 7 years, 13) Test Reports – 7 years.

**36. SEAMED PIPE**

Due to the potential high pressure that may be experienced in the mission profile environment, the delivery of seamed pipe is prohibited. Suppliers shall only deliver seamless pipe on AMETEK SCP purchase orders.

**37. ACCEPTABLE MATERIAL SUBSTITUTIONS**

Commercial specifications that are equivalent or have replaced military/federal specifications must first be approved by AMETEK SCP prior to substitution.

**38. CONTROL OF UNCLASSIFIED GOVERNMENT DOCUMENTS ISSUED FOR A PURCHASE ORDER (PO)**

When this clause is invoked, the documentation distributed with the PO is to be handled and secured in a manner as defined herein. Documentation associated with this PO cannot be viewed by anyone that is not a US citizen or a Lawful Permanent Resident of the US/USA without permission flow-down from the US Department of State.

The documentation that was distributed by AMETEK SCP, or for AMETEK SCP by another government agency, does not carry a US security classification; however specific notifications on the drawing provide knowledge in regards to handling.

- If the document has a “Distribution Statement ‘B, C, D, E, or F’”, *example* –DISTRIBUTION STATEMENT D. Distribution authorized to Department of Defense and U.S. DoD contractors only- (or similar wording) the document should be filed from view when not in use. Putting the hardcopy document in a folder, file, draw, etc.; so it is not visible, is sufficient provided the building is secured. If the building is open to the public then it is recommended the document be stored in a manner that is not accessible to the public providing at least one barrier (locked file, room, etc.). If the document is electronic it must be stored in a protected manner providing at least one barrier from public access.



## PROCUREMENT QUALITY CLAUSES: PQC-1

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

An active firewall is considered a protective barrier from the internet. A secured folder on an internal file server that eliminates public access is a protective barrier. These unclassified documents shall not be distributed electronically to others without AMETEK SCP knowledge to ensure proper controls are maintained.

- Management of unclassified documents after intended use is complete: Unclassified documents marked with Distribution Statements B, C, D, E, or F shall be destroyed by any method that will prevent disclosure of contents or reconstruction of the document. When local circumstances or experience indicates that this destruction method is not sufficiently protective of the information, local authorities may prescribe other methods but must balance the additional expense against the degree of sensitivity.
- If the document has an ITAR stamp or statement (aka Export Control) the document cannot be viewed by anyone that is not a US citizen or a Lawful Permanent Resident of the US/USA without permission flow-down from the US Department of State. The document controls established for Distribution Statement unclassified documents apply.
- The supplier is obligated to maintain compliance with DOD Directive 5230.24. It is the supplier's responsibility to understand the DOD Directive and to verify the current revision at the time of purchase order placement. <http://www.dtic.mil/whs/directives/>

### 39. **COUNTERFEIT PARTS PREVENTION:**

The requirements (definitions) of the United States Federal Acquisition Regulation (FAR) 52.211-5 are hereby applied (in its current form at time of order). A link to "FARSite" is at the bottom of the clause, it is the Sellers responsibility to understand the FAR clause and to verify the current revision at the time of purchase order placement.

For Level 1/SUBSAFE components/materials the FAR 52.211-9005 Conditions for evaluation and acceptance of offers for critical safety items applies (in its current form at time of order).

When this clause is invoked the Seller is obligated to ensure that the material(s) being delivered are new and authentic. To exhibit that the materials are new and authentic the Seller shall, when requested, provide traceability of the material(s) back to the Original Component Manufacturer (OCM) or the Original Equipment Manufacturer (OEM), this includes mills and foundries. When requested by AMETEK SCP it is the Sellers responsibility to provide documented traceability that presents complete and compelling support that the materials procured/provided are legitimate and not misrepresented in any manner. AMETEK SCP functions under the laws of the United States (US/USA) with the knowledge that these laws and regulations are subject to change without notice. It is the Sellers responsibility to understand the meanings and implication of fraud, falsification and misrepresentation regarding material(s) and documentation as it applies.

FAR/DFAR: <http://farsite.hill.af.mil/>

### 40. **SUPPLY CHAIN RISK:**

When this clause is invoked the performance of the purchase order is for a Government Contract that has imposed DFAR 252.239-7018 SUPPLY CHAIN RISK.

## PROCUREMENT QUALITY CLAUSES: PQC-1

*AMETEK SCP, Inc. is an equal opportunity employer. The equal opportunity clauses at 41CFR60-1.4, 41CFR60-250.5 and 41CFR60-741 are incorporated by reference.*

---

The following is an excerpt of the DFAR at the time of this writing. It is the supplier's responsibility to understand the clause as provided by the US Government at the time of the purchase order acceptance. A link to "FARSite" is at the bottom of the clause. These requirements are to be flowed down to sub-tier suppliers.

- (a) "Supply chain risk," means the risk that an adversary may sabotage, maliciously introduce unwanted function, or otherwise subvert the design, integrity, manufacturing, production, distribution, installation, operation, or maintenance of a national security system (as that term is defined at 44 U.S.C. 3542(b)) so as to surveil, deny, disrupt, or otherwise degrade the function, use, or operation of such system.
- (b) The Contractor shall maintain controls in the provision of supplies and services to the Government to minimize supply chain risk.
- (c) In order to manage supply chain risk, the Government may use the authorities provided by section 806 of Pub. L. 111-383. In exercising these authorities, the Government may consider information, public and non-public, including all-source intelligence, relating to a Contractor's supply chain.
- (d) If the Government exercises the authority provided in section 806 of Pub. L. 111-383 to limit disclosure of information, no action undertaken by the Government under such authority shall be subject to review in a bid protest before the Government Accountability Office or in any Federal court.
- (e) The Contractor shall include the substance of this clause, including this paragraph (e), in all subcontracts involving the development or delivery of any information technology, whether acquired as a service or as a supply.

FAR/DFAR: <http://farsite.hill.af.mil/>

### 41. **EFFECTIVE REVISIONS OF SPECIFICATIONS (GDEB ORDERS ONLY)**

The effective revisions of invoked specifications shall be determined as follows:

- a) When a revision is cited in the purchase order, only that revision shall be used. An earlier revision of a specification may be used only when both the invoked and earlier revision, and all revisions in between, are listed in EB2P756 located at (<http://www.gdeb.com/suppliers/eb2p756.pdf>) with an interchangeability code of \*.
- b) When a revision is not cited in the purchase order, any revision listed in EB2P756 may be used.
- c) When a specification is not cited in either the purchase order or EB2P756, any issued revision may be used.

(Note: When EB2P756, the NSSF/SSGN specification effectivity index, is referred to above, the supplier may use any version which has been provided by the buyer, not to be dated any earlier than 6 months prior to the date of the applicable purchase order.)

### 42. **NOT USED**