

Military & Commercial Aerospace



**HERMETIC
SEAL™**

AMETEK®

INTERCONNECT TECHNOLOGIES

*A leading provider of interconnect
solutions for harsh environments since
1945*

HTX—High Temperature Hermetic Connector



- **Temperature range -197°C to +440°C (-322°F to +824°F)**
- **Hermetic Leak Rate of 1×10^{-9} cc/sec of Helium at 15 PSI**
- **Available in shells and insert arrangements that meet the requirements of several MIL Specifications**

HTX—High Temperature Hermetic Connector

HTX—Hermetic Seal's answer to Extreme Harsh Environment Mated Pair Hermetically Sealed Interconnects!

Incorporating the latest Material Science, HSC has developed the next generation of Extreme High Temperature & High Vibration Interconnect system

- ◇ Temperature range -197°C to +440°C (-322°F to +824°F)
- ◇ Compatible to any Mil-Standard or Customer Specific Design
- ◇ Superior and Stable Electrical Performance (IR)
 - >5,000 Megohms @ 1,000 VDC @ room temperature
 - >1,000 Megohms @ 1,000 VDC @ 800°F
- ◇ Vibration @ 440 C exceeding 60 g's @ 3,000 Hz
- ◇ Hermeticity 1×10^{-9} CC/Sec at 1 atmosphere



**HERMETIC
SEAL™**

Hermetic Seal Corporation
4232 Temple City Blvd
Rosemead, CA 91770 USA
Ph (626) 443-8931
Fx (626) 443-6610
www.hermeticseal.com

AMETEK®
INTERCONNECT TECHNOLOGIES